

# Optical Connectors

## Field Installable Connectors (Fusion Splice Type)

### Lynx-CustomFit™ Splice-On Connector Ver.2

Splice-on fiber optic connector enabling quick, easy and reliable permanent field terminations

- Eliminating crimping process and crimping tools
- Requires neither adhesives, hand polishing, nor matching gel
- Compatible with Sumitomo Splicers and other brands
- Can apply for the place required low return loss as analog transmission, etc.
- Can apply for wide temperature range.

	SC	LC	FC	ST	Q8MPO / 12MPO
Interface standard	IEC61754-4	IEC61754-20	IEC61754-13	IEC 61754-2	IEC61754-7-1
Insertion Loss (against master plug)	SMF: Ave.0.2dB, Max. 0.3dB MMF: Ave.0.1dB, Max. 0.25dB				SMF,MMF Low Loss (LL) Max. 0.4dB SMF Standard Loss Max. 0.75dB
Return Loss (against master plug)	SMF: ≥ 60dB (APC), ≥ 55dB (UPC) MMF: ≥ 30dB (PC)				SMF: ≥ 55dB

#### Lineup for Single fiber connector

Connector type	Polishing type	fiber type	Connector Color	fiber / Cord diameter	Boot type
SC LC FC ST <sup>1</sup>	APC	SM	Green	250 / 900μm Tight Buffer	Standard boot Short boot <sup>2</sup>
	UPC	SM	Blue	900μm Loose Buffer	
	PC	MM50(OM2)	Black	2mm with 900μm Tight Buffer	
		MM50(OM3)	Aqua	2mm with 900μm Loose Buffer	
		MM62.5(OM1)	Beige	3mm with 900μm Tight Buffer	

\*1 ST connector is available for SM(UPC polishing) and MM(PC polishing).  
\*2 Short boot is available for SC and LC type of 250 / 900 μm tight buffer.


#### Lineup for MPO connector

Guide Pin	fiber/Polishing type	Connector color	Cord diameter
With / Without guide pin	SM Low loss	Yellow	RBN: 8c/12c Bare Ribbon
	SM Standard loss	Green	RND: 8c/12c Round cord (φ3mm)
	MM50(OM2) Low loss*	Black	RBC: 8c/12c Ribbon cord
	MM50(OM3) Low loss	Aqua	

\*MM50(OM2) Low Loss type is available for 12c(12-fiber).




#### Structure



### e-SC Fusion™ Connector

- Compatible with the rectangular drop cable.
- No crimping process and crimping tools.



#### Assembly Tools

Fiber cleaver	Jacket remover	Kevlar snips	Cable Holder


e-SC Fusion™ Connector	
Ordering Code	ESCF-SC/APC      ESCF-SC/UPC
Fiber Type	SM
Applicable Cable	Indoor Cable/Drop Cable 1.6×2.0 to 2.0×3.1 (mm)
Polish	APC      UPC
Insertion Loss	SM: Typ. ≤ 0.15dB, Max. ≤ 0.3dB (against master plug)
Return Loss	SM: ≥ 60dB (APC), ≥ 50dB (UPC) (against master plug)
Operating Temperature	-40 to +75°C
Housing Color	SM,APC Green      SM,UPC Blue
Interface	IEC 61754-4
Qualification	IEC 61753-1 Cat.OP

## Field Installable Connectors (Fusion Splice Type)

### Assembly procedures



### Connector Kit



Assembly procedure video



There is the case that an address is changed without a notice and cannot watch.

### Assembly Tools

Tool Name [Part No.]		An appropriate Sumitomo Electric fusion splicer	Fiber cleaver [FC-8R-MC]	Jacket remover [JR-MO3]	Hot jacket remover [JR-6+]	Sheath splitter [LYNX-CORDTOOL-1.6-2.4]	Sheath splitter [LYNX-CORDTOOL-2.0-3.0]	Kevlar snips [N-57]	ST assembly tool [LYNX2-ST-ASSEMBLY-TOOL]
Appearance									
Single Fiber	Cord	● with all current models	●	●	—	● for 1.6 / 2.4mm cord	● for 2 / 3mm cord	●	● for ST connector
	Fiber		●	●	● for 0.2-0.4mm fiber	—	—	—	● for ST connector
MPO	RoundCord/RibbonCord	● with ribbon fiber splicer [TYPE-72M12]	●	—	●	—	● for round cord / ribbon cord	●	—
	Bare Ribbon		●	—	●	—	—	—	—

### Fiber holders for single fiber connector

Type	Left side (setting fiber / cord)	Right side (setting ferrule sub-assembly)
250μm fiber	FHS-025 LYNX2-S-LB5(2MM)	LYNX2-C (Plastic, Standard) * LYNX2-UML-C (Metal, Option)
900μm Tight Buffer	FHS-09 LYNX2-UML-S	
900μm Loose Buffer	LYNX2-S-LB5(2MM)	
2mm cord with 900μm Tight Buffer	LYNX2-UML-S	
2mm cord with 900μm Loose Buffer	LYNX2-S-LB5(2MM)	
3mm cord with 900μm Tight Buffer	LYNX2-UML-S	

\* 1 pc of LYNX-C holder is supplied with every 100 connectors.

### Fiber holders for MPO connector

Type	Left side (setting fiber / cord)	Right side (setting ferrule sub-assembly)
Bare Ribbon	12-fiber: FHM-12V 8-fiber: FHM-8	LYNX2-C(MT) (Plastic, Standard) * LYNX2-C(MT) Metal (Metal, Option)
Round Cord		
Ribbon Cord		

\* 1 pc of LYNX2-C(MT) holder is supplied with every 100 connectors.

### Lynx2-Duplex-LC-Clip

#### Lynx2-LC turns into Duplex type easily

- One piece, Simple design
- Easy installation and detachable design
- Lynx2-LC for 250/900μm, 900μm LB, 1.6mm and 2mm types are available
- Clip size: W13.4mm × H12.6mm



Note: In case of the optical cord with 2.4mm or larger diameter, please ask the ordering code of the connector.

### Lynx2 with Short Boot

#### Compact size for small cabinet

- Short Silicone Boot
- Lynx2-SC and LC for 900μm types are available

